

Amendment to the claims:

Claims 1-14 (canceled)

Claims 15-21 (withdrawn)

Claim 22 (new) A holster for handguns having a barrel and a trigger guard in which the handguns are held by the trigger guard comprising:

a tubular assembly comprising: an elongated first structure that functions as a left side wall having an outer surface, an inner surface and a top end; an elongated second structure functions as a right side wall having an outer surface, an inner surface and a top end; an elongated third structure that functions as a front wall having an outer surface, an inner surface and a top end; and a fourth structure that functions as an elongated rear wall having an outer surface, an inner surface and a top end;

said top end of said fourth structure being downwardly displaced from said top end of said first structure and said top end of said second structure to form a recess for capturing a trigger guard of a handgun;

an elongated retention pin having an inner end, an outer end, surrounding side walls extending from said inner end to said outer end and a longitudinally extending X-axis; and

means for supporting said retention pin and reciprocally moving said retention pin into said recess for capturing a trigger guard of a handgun therein and preventing removal therefrom; said means comprising a sliding actuator having a longitudinally extending Y-axis; said sliding actuator being mechanically interfaced with said retention pin in such a manner as to allow said retention pin to be withdrawn from a handgun trigger guard when it is positioned in said recess by pushing said sliding actuator along said Y-axis that is substantially perpendicular to said X-axis of said retention pin.

23 (new) A holster for handguns as recited in claim 22 wherein said sliding actuator is wedge-shaped.

24 (new) A holster for handguns as recited in claim 22 further comprising first spring means contacting said retention pin and spring loading said retention pin in the direction for capturing a handgun trigger guard when it is positioned in said recess.

25 (new) A holster for handguns as recited in claim 22 wherein said inner end of said retention pin is beveled toward said top end of said holster.

1 26 (new) A holster for handguns as recited in claim 22 wherein said sliding actuator has a tapered
2 fork configuration.

3 27 (new) A holster for handguns as recited in claim 22 further comprising first safety lock means
4 that prevents sliding movement of said sliding actuator until said first safety lock means is disengaged.

5 28 (new) A holster for handguns as recited in claim 27 wherein said first safety lock means
6 comprises a sliding mechanism that must first be moved before said sliding actuator can be pushed.

7 29 (new) A holster for handguns as recited in claim 27 further comprising remote means for
8 releasing said first safety lock means.

9 30 (new) A holster for handguns as recited in claim 27 wherein said first safety lock means further
10 comprises means for identifying the authorized user of said holster.

11 31 (new) A holster for handguns as recited in claim 22 further comprising an elongated safety
12 strap having a first end and a second end and both of said ends are pivotally secured to opposite lateral side
13 walls of said holster; said safety strap being pivotal from a first security position which inhibits removal of
14 a handgun from said holster, to a second position substantially free of the handgun thus allowing the
15 handgun to be withdrawn from said holster.

16 32 (new) A holster for handguns as recited in claim 31 further comprising means for actuating
17 pivotal motion of said safety strap.

18 33 (new) A holster for handguns as recited in claim 22 further comprising an elongated safety
19 strap having a first end and a second end and both of said ends having snap fastener means securing them
20 to opposite sides of said holster to inhibit removal of a handgun from said holster.

21 34 (new) A holster for handguns as recited in claim 33 further comprising a formed releasing
22 element shaped to release at least one of said snap fastener means using a generally downward motion of
23 user's hand.
24
25
26
27
28
29
30